




profondità scavi / depth of excavation 60 cm.

profondità scavi / depth of excavation 50 cm.

staffa antitrauma sfuso / bracket for loose safety matting

modifiche / amendments :				scala / scale : -		misure espresse in / dimensions are established in : CM.						
nr°	data/date	pos	descrizione/description	firma sign	In tolleranze generali applicate / general tolerances : • sezione/diametro legname impregnato 8,5 (cm) • lunghezza legname impregnato 3,0 (length, total) • lavorazione legname impregnato 8,2 (cm) • componenti in metallo 1 (mm) • componenti in materiali plastici 1,5 (mm)		le colorazioni dei componenti refrigeranti sono solo indicative e potranno variare a noi/ discrezione. Il presente elaborato grafico è da ritenersi indicativo. La sua reale fattibilità deve essere preventivamente verificata in loco prima della conferma d'ordine. Nessuna responsabilità pertanto sarà da attribuirsi alla scrivente. The colours that are visible in the rendering are just illustrative and can be modified. The graphic design as well is illustrative, and customers are compelled to verify the equipment's real feasibility before finalizing the order. We do not accept claims for similar themes.		denom. / name :	pianta scavi / excavation plant		
01									nr. ds. / draft nr. :	4792	codice / code :	xt205t
02									luogo / place :	Mezzolombardo		
03											data / date :	26/07/18
03									esecuzione/verifica/ approvazione : created/checked/ approved by :			